

ONE-HUNDR LEGISLATURE Е D

Legislative Document

S. P. 210

In Senate, January 19, 1961

Referred to Committee on Transportation. Sent down for concurrence and ordered printed.

CHESTER T. WINSLOW, Secretary Presented by Senator Ferguson of Oxford.

STATE OF MAINE

IN THE YEAR OF OUR LORD NINETEEN HUNDRED SIXTY-ONE

AN ACT Relating to Weight of Certain Commercial Vehicles.

Be it enacted by the People of the State of Maine, as follows:

R. S., c. 22, § 109, amended. The 2nd paragraph of section 109 of chapter 22 of the Revised Statutes, as amended by section 2 of chapter 309 of the public laws of 1957, is further amended to read as follows:

'Two or more axles less than 4 feet apart shall be considered as one axle and no group of axles shall carry a load in pounds in excess of the value given in the following table corresponding to the distance in feet between the extreme axles of the group, measured longitudinally to the nearest foot:

Distance in feet between the extremes of any group of axles	Maximum load in pounds carried on any group of axles	
3	axle vehicles	4 or more axle vehicles with adequate brakes on the wheels of all axles
4 to 7, inclusive	32,000	
8		
9	33,580	
IO	34,550	
II	00.0	
I2	36,470	
13		
14	38,360	45,900
15	39,300	46,750
16	40,230	47,600

No. 543

3	axle vehicles	4 or more axle vehicles with adequate brakes on the wheels of all axles
17	41,160	48,450
18	42,080	49,300
19	42,990	50,150
20	43,900	51,000
21	44,800	51,850
22	45,700	52,700
23	46,590	53,550
24	47,470	54,400
25	48,350	55,525
26	49,220	56,100
27	50,000	56,950
28	50,000	57,800
29	50,000	58,650
30	50,000	59,520
31 and over	50,000	60,000

provided, however, that no vehicle shall have a gross weight imparted to any road surface of more than 22,000 pounds on any one axle, and no vehicle having 2 or more axles less than 8 feet apart shall be operated, or caused to be operated, with more than 18,000 pounds imparted to the road surface from either axle or 32,000 36,000 pounds from both axles; provided further, that no vehicle shall be so operated, or caused to be operated, when the load imparted to the road surface is greater than 600 pounds per inch width tire, manufacturer's rating; except, however, that 3-axle trucks with brakes on the wheels of all axles hauling forest products may be operated for a gross weight of 48,000 pounds with a distance between the extreme axles of not less than 18 feet, and except, further, that 3-axle trucks with brakes on the wheels of all axles hauling construction materials may be operated for a gross weight of 48,000 pounds with a distance between the extreme axles of not less than 16 feet and except that in special cases, special permits for the transportation of individual shipments in loads of greater gross weights may be granted by the State Highway Commission or such appropriate commission or official as is duly authorized elsewhere in this chapter. All trucks with 4 or more axles shall have adequate brakes on the wheels of all axles.'