

# MAINE STATE LEGISLATURE

The following document is provided by the  
**LAW AND LEGISLATIVE DIGITAL LIBRARY**  
at the Maine State Law and Legislative Reference Library  
<http://legislature.maine.gov/lawlib>



Reproduced from scanned originals with text recognition applied  
(searchable text may contain some errors and/or omissions)

---

---

# ONE - HUNDREDTH LEGISLATURE

---

---

## Legislative Document

No. 611

H. P. 436

House of Representatives, January 19, 1961

Referred to Committee on Transportation. Sent up for concurrence and ordered printed.

HARVEY R. PEASE, Clerk

Presented by Mr. Berman of Auburn.

---

---

## STATE OF MAINE

---

IN THE YEAR OF OUR LORD NINETEEN HUNDRED  
SIXTY-ONE

---

### AN ACT Relating to Weight of Certain Three-Axle Trucks.

---

Be it enacted by the People of the State of Maine, as follows:

**R. S., c. 22, § 109, amended.** The 2nd paragraph of section 109 of chapter 22 of the Revised Statutes, as amended by section 2 of chapter 309 of the public laws of 1957, is further amended to read as follows:

‘Two or more axles less than 4 feet apart shall be considered as one axle and no group of axles shall carry a load in pounds in excess of the value given in the following table corresponding to the distance in feet between the extreme axles of the group, measured longitudinally to the nearest foot:

Distance in feet between the extremes of any group of axles	Maximum load in pounds carried on any group of axles	
	3 axle vehicles	4 or more axle vehicles with adequate brakes on the wheels of all axles
4 to 7, inclusive . . . . .	32,000	
8 . . . . .	32,610	
9 . . . . .	33,580	
10 . . . . .	34,550	
11 . . . . .	35,510	
12 . . . . .	36,470	
13 . . . . .	37,420	
14 . . . . .	38,360	45,900
15 . . . . .	39,300	46,750
16 . . . . .	40,230	47,600

Distance in feet between the extremes of any group of axles	Maximum load in pounds carried on any group of axles	
	3 axle vehicles	4 or more axle vehicles with adequate brakes on the wheels of all axles
17 .....	41,160	48,450
18 .....	42,080	49,300
19 .....	42,990	50,150
20 .....	43,900	51,000
21 .....	44,800	51,850
22 .....	45,700	52,700
23 .....	46,590	53,550
24 .....	47,470	54,400
25 .....	48,350	55,250
26 .....	49,220	56,100
27 .....	50,000	56,950
28 .....	50,000	57,800
29 .....	50,000	58,650
30 .....	50,000	59,520
31 and over .....	50,000	60,000

provided, ~~however~~ that no vehicle shall have a gross weight imparted to any road surface of more than 22,000 pounds on any one axle, and no vehicle having 2 or more axles less than 8 feet apart shall be operated, or caused to be operated, with more than 18,000 pounds imparted to the road surface from either axle or 32,000 pounds from both axles; provided further, that no vehicle shall be so operated, or caused to be operated, when the load imparted to the road surface is greater than 600 pounds per inch width tire, manufacturer's rating; except ~~how-~~  
~~ever~~ that 3 axle trucks with brakes on the wheels of all axles hauling forest products may be operated for a gross weight of 48,000 pounds with a distance between the extreme axles of not less than 18 feet, and except ~~further~~ that 3-axle trucks with brakes on the wheels of all axles hauling construction materials may be operated for a gross weight of 48,000 pounds with a distance between the extreme axles of not less than 16 feet **and except that 3-axle trucks with brakes on the wheels of all axles hauling agricultural products, including seed, feed and fertilizer, may be operated for a gross weight of 48,000 pounds with a distance between the extreme axles of not less than 16 feet** and except that in special cases, special permits for the transportation of individual shipments in loads of greater gross weights may be granted by the State Highway Commission or such appropriate commission or official as is duly authorized elsewhere in this chapter. All trucks with 4 or more axles shall have adequate brakes on the wheels of all axles.'