

## (After Deadline) FIRST REGULAR SESSION

## ONE HUNDRED AND THIRTEENTH LEGISLATURE

## Legislative Document

NO. 1133

H.P. 842 House of Representatives, April 7, 1987 Approved for introduction by a majority of the Legislative Council pursuant to Joint Rule 27.

Reference to the Committee on Transportation suggested and ordered printed.

EDWIN H. PERT, Clerk

Presented by Representative RUHLIN of Brewer. Cosponsored by Representatives DUFFY of Bangor, STROUT of Corinth and Senator DOW of Kennebec.

## STATE OF MAINE

IN THE YEAR OF OUR LORD NINETEEN HUNDRED AND EIGHTY-SEVEN

1 AN ACT to Ensure Rail Safety When Operating 2 a Freight Train without a Caboose. 3 Δ Be it enacted by the People of the State of Maine as follows: 5 6 23 MRSA §4218, sub-§2-A is enacted to read: 7 2-A. Caboose. A caboose is not required on freight trains, if all the following conditions 8 are 9 satisfied: Flag protection against following trains on 10 Α. 11 the same track is not required; 12 в. The track route is equipped with wayside 13 overheated journal and dragging equipment detec-

Page 1-LR2123

tors located along that route, at intervals not 1 exceeding 30 miles in distance, which are able to communicate directly to the train's operating crew, information related to the safety of that 2 3 4 train's operation, including acknowledgement of 5 the train's presence at the detector, the nature of defect found and the location within the train 6 7 8 of any defect detected; C. The track route is equipped with high or shifted load detectors in advance of locations where it can reasonably be foreseen that a high 9 10 11 12 or shifted load could cause an unsafe condition 13 when moving through such locations; 14 an operating telemetry device lo-There is D. cated on the trailing end of the rearmost car ca-15 16 pable of communicating the following information to the locomotive engineer: 17 (1) Motion; 18 19 (2) Brakepipe pressure; and 20 (3) Power condition of the transmitting de-21 vice; 22 There is a counting device which enables the 23 locomotive engineer to ascertain the length of 24 the train; and 25 F. There are no cars containing open top loads 26

which exceed the railway's line clearances, as
published annually by the National Railway Publication Company in their publication Railway Line
Clearances, placed farther than 2,000 feet behind
the controlling locomotive.

31 Each railroad corporation operating in the State 32 shall comply with the provisions of this subsection 33 no later than 6 months after the effective date of 34 this subsection.

35 Any person or railroad corporation who fails to com-96 ply with this subsection commits a civil violation 97 for which a forfeiture of \$200 may be adjudged for 98 each violation.

Page 2-LR2123

The purpose of this bill is to ensure to some degree the safety of the citizens who work or reside near railroads from being exposed to unnecessary risks, by establishing those conditions which must be met to operate a train without a caboose.

2123031687

23456

7

ż;

Page 3-LR2123

1