



	L.D. 1702
2	DATE: 2/8/6 (Filing No. H-749)
4	•
6	TRANSPORTATION
8	
10	Reproduced and distributed under the direction of the Clerk of the House.
12	
14 16	STATE OF MAINE HOUSE OF REPRESENTATIVES 122ND LEGISLATURE SECOND REGULAR SESSION
10	
18	COMMITTEE AMENDMENT 'A" to H.P. 1209, L.D. 1702, Bill, "An
20	Act To Increase Efficiency in Truck Hauling"
22	Amend the bill by striking out all of section 1 (page 1, lines 18 to 30 in L.D.) and inserting in its place the following:
24	
26	' Sec. 1. 29-A MRSA §2390, sub-§1, ¶J, as amended by PL 2005, c. 170, §2, is further amended to read:
28	J. Notwithstanding any other provision of this subsection, a single semitrailer whose total structural length exceeds
30	48 feet but does not exceed 53 feet may be operated in combination with a truck tractor on a highway network and
32	access systemdesignated bytheCommissionerof Tfansportation if the following conditions are met.
34	(1) The wheelbase of the semitrailer, measured as the
36	distance from the kingpin to the center of the rearmost axle of the semitrailer, may not exceed 43 feet.
38	
40	(2) The kingpin setback of the semitrailer, measured as the distance from the kingpin to the front of the semitrailer, may not exceed 3 1/2 feet in length.
42	
44	(3) The rear overhang of the semitrailer, measured as the distance from the center of the rear tandem axles of the semitrailer to the rear of the semitrailer, may
46	not exceed 35% of the wheelbase of the semitrailer.

.

Page 1-LR2607(2)

COMMITTEE AMENDMENT

COMMITTEE AMENDMENT "A" to H.P. 1209, L.D. 1702

2

4

6

8

10

12

14

16

40

(4) The semitrailer must be equipped with a rear underride guard that is of sufficient strength to prevent a motor vehicle from penetrating underneath the semitrailer, extends across the rear of the semitrailer to within an average distance of 4 inches of the lateral extremities of the semitrailer, exclusive of safety bumper appurtenances, and is placed at a height not exceeding 22 inches from the surface of the ground as measured when the semitrailer is empty and is on a level surface.

(5)The semitrailer must be equipped with vehicle lights that comply with or exceed federal standards and reflective material approved by the Commissioner of Transportation that must be located on the semitrailer in a manner prescribed by the commissioner. The semitrailer must display a conspicuous warning on the rear of the semitrailer indicating that the vehicle 18 combination has a wide turning radius. 20

(8) Except as provided in subparagraph (10), the 22 overall length of the truck tractor and semitrailer combination of vehicles traveling beyond the national 24 network may not exceed 74 feet, including all permanent structural parts of the vehicle, or 26 temporary, and any load carried on or in the vehicle. For the purposes of this subparagraph, "national network" means those highways in the State identified 28 under 23 Code of Federal Regulations, Appendix A to 30 Part 658.

32 (9) Notwithstanding section 2380, the width of the semitrailer must be 102 inches, except that the width of the rear safety bumper and appurtenances to the 34 safety bumper may not exceed 103 inches and except that 36 the width of a flatbed or lowboy semitrailer, measured as the distance between the outer surface edges of the 38 semitrailer's tires, must be at least 96 inches but no more than 102 inches.

For-vehicles with -a-length-that -dees-not-exceed (10) 42 74-feet,-including-all-structural-parts-of-the-vehicle, permanent-or-temporary,-and-any-load-earried-on-or-in 44 the-vehicle,-access-is-permitted-to-service-facilities or-terminals-within-one-mile-of-the-highway-network-and 46 access -- system -- designated -- by -- the -- Commissioner -- of Transportation--for--53-foot-cemitrailer--traffic----For 48 operations--of--these--vehicles-to--terminals-beyond--the one-mile--distance,--an--access--permit--specifying--the 50 meter-carrier,-specific-routing-and-terminal-location

Page 2-LR2607(2)

COMMITTEE AMENDMENT

COMMITTEE AMENDMENT 'A" to H.P. 1209, L.D. 1702

must-be-obtained-from-the-Department-of-Transportation and-carried-in-the-truck-tractor. For vehicles whose overall length exceeds 74 feet, including all structural parts of the vehicle, permanent or temporary, and any load carried on or in the vehicle, access is permitted to service facilities or terminals within one mile of the national network. For purposes of this subparagraph, "national network" means those highways in the State identified under 23 Code of Federal Regulations, Appendix A to Part 658.

- 12 (12) This vehicle combination may not transport cargo that has been prohibited for this vehicle combination
 14 by the Commissioner of Transportation.
- 16 (13) This paragraph does not apply to a trailer or semitrailer when transporting or returning empty from transporting a nondivisible load or object under the provisions of an overlimit permit granted by section 20 2382.
- 22 The-Secretary-of-State-shall-adopt-rules-for-the-permitting of-this-vehicle-combination.
- Nothing in this paragraph limits the authority of the department under Title 23, section 52 to adopt rules prohibiting or limiting access by semitrailers or other vehicles to a highway or portion of a highway or other segment of the transportation infrastructure in order to an ensure public safety.'
- 32

34

24

<u>, 8</u> 8,

2

4

б

8

10

SUMMARY

This amendment eliminates the 53-foot access system designated by the Commissioner of Transportation, allowing a 36 single semitrailer whose total structural length exceeds 48 feet 38 but does not exceed 53 feet to be operated in combination with a truck tractor on the highway network if safety standards and 40 conditions are met. The amendment also clarifies the Department of Transportation's rule-making authority to limit or prohibit 42 access by semitrailers to certain highways to ensure safety.

Page 3-LR2607(2)

COMMITTEE AMENDMENT