



125th MAINE LEGISLATURE

FIRST REGULAR SESSION-2011

Legislative Document

No. 442

H.P. 335

House of Representatives, February 10, 2011

An Act To Allow Year-round Placement of Cobble-trapping Fences behind Established Seawalls

Reference to the Committee on Environment and Natural Resources suggested and ordered printed.

fleth & Fuit

HEATHER J.R. PRIEST Clerk

Presented by Representative CHASE of Wells. Cosponsored by Senator COLLINS of York and Representatives: AYOTTE of Caswell, BENNETT of Kennebunk, CEBRA of Naples, GILLWAY of Searsport, McKANE of Newcastle, VALENTINO of Saco, Senators: HOBBINS of York, SHERMAN of Aroostook.

Printed on recycled paper

1	Be it enacted by the People of the State of Maine as follows:
2	Sec. 1. 38 MRSA §480-II is enacted to read:
3	<u>§480-II. Cobble-trapping fence in a coastal sand dune system</u>
4 5	This section applies to the placement of a cobble-trapping fence in a coastal sand dune system.
6 7	1. Definitions. As used in this section, the following terms have the following meanings.
8	A. "Cobble" means a rock that is smaller than a boulder and larger than gravel.
9 10	B. "Cobble-trapping fence" means a fence that is designed to prevent cobbles from passing through it.
11 12 13 14	2. Permit. Notwithstanding anything to the contrary in this article, the department may issue a permit to an owner of property in a coastal sand dune system to construct, repair or replace a year-round cobble-trapping fence landward of an existing seawall in a developed area if:
15 16 17	A. The property is adjacent to a beach with gravel and cobble sediment and has a developed area, such as a lawn, between a building on the property and the beach; and
18	B. The fence:
19	(1) Is not located on a naturally vegetated frontal dune;
20 21	(2) Is located seaward of the foundation of a building on the property and is no more than 15 feet in front of the building;
22 23	(3) On either side, does not extend more than 2 feet beyond the foundation of a building on the property;
24	(4) Does not consist of more than one row of fencing;
25	(5) Does not have openings smaller than 2 inches square;
26	(6) Is not higher than 4 feet above grade; and
27	(7) Is not supported by a permanent, continuous footing.
28 29 30	A cobble-trapping fence may be supported by permanent, small subsurface pipes or similar emplacements. Cobbles and sediment trapped by a cobble-trapping fence may be removed and placed immediately seaward of a frontal dune or seawall on the property.
31	SUMMARY
32 33	This bill authorizes the use of cobble-trapping fences on a year-round basis and sets conditions on their use.